

Features:

- Provides a multiple function USB powered product comprising a programmable fixed frequency or tuneable and switchable P-Band (280 MHz to 320 MHz) and S-Band (2.2 GHz to 2.4 GHz) PCM/FM Telemetry Receiver combined with a Bit Synchroniser and Decommulator
- The APK8767-3PS can be operated as:
 - Combined Receiver, Bit Synchroniser and Decommulator
 - Receiver and Bit Synchroniser
 - Bit Synchroniser and Decommulator
 - Bit Synchroniser
 - PCM Decommulator
- Provides clock and data recovery from a received serial PCM data stream over a Bit Rate range extending from 15000 BPS to 5 MBPS
- Receiver Frequency, Bit Rate and Frame Format set up through a USB 2 Port by a host PC
- Fixed Frequency and Bit Rate Options are available
- Provides Decommuted data transfer to the host PC through the same USB 2 Port
- Powered from the Host PC through the USB 2 port
- Processes PCM Codes including NRZ, RNRZ and Bi-Ø codes
- RS422 Data and Clock Input facility
- Buffered non-isolated RS422 Data and Clock Outputs
- IRIG B Time Code Reader facility
- Set-Up information and Frame Format stored in non-volatile memory
- Supports IRIG 106 PCM Frame Formats
- Supplied with GDSmate Set up, display, archiving and export software



The Apollotek APK8767-3PS is a Dual Band Multi-Function PCM/FM Telemetry Receiver, Bit Synchroniser and Decommulator. The APK8767-3PS is one of a series of Apollotek unique USB products designed for Telemetry, PCM Flight Test Instrumentation system checkout, test and evaluation and Data Link applications. The Unit is packaged into an aerospace grade aluminium housing machined from solid to enable the unit to be used in both ground based and airborne applications.

The Receiver Frequency, Bit Rate, Loop Bandwidth, Tracking Range and Frame Format parameters are set up through a USB 2 port connection to a host PC running the USB version of the Apollotek GDSmate Telemetry Environment Software package provided with the unit.

The APK8767-3PS utilises proprietary Apollotek developed analogue and digital signal processing techniques to extract clock and synchronised data from a perturbed baseband serial PCM data stream and to provide PCM Decommulation with data transfer to a host PC through a high speed serial USB port. The APK8767 unit is powered through the host PC USB Port.

Input Signal and Stream Lock status is provided on the unit by multicolour LED indicators. Status information is also provided to the host PC through the USB port.

The APK8767-3PS can be operated as a combined Receiver, Bit Synchroniser and Decommulator and the unit can also be operated as a Bit Synchroniser, a combined Bit Synchroniser and Decommulator and just as a PCM Decommulator.

RECEIVER, BIT SYNCHRONISER and DECOMMUTATOR SPECIFICATIONS

Receiver Tuning Ranges:	P-Band with standard 280 MHz to 320 MHz and S-Band 2200 MHz to 2400 MHz Software Switchable tuning ranges Fixed Frequency and data rates can be programmed.
Receiver Sensitivity	Nominal -85 dBm
Bit Sync Data Rates	15000 BPS to 5 MBPS for NRZ-L Codes
Bit Sync Input PCM Codes	NRZ-L/M/S, RNRZ-L ($2^{11,15,17,20,23}$), BIØ-L/M/S
Decommulator Formats	Compatible with IRIG 106 Chapter 4 Frame Format definitions
IRIG B Time Code Input	1 Volt rms modulated time code input into 600 Ohms impedance
Input and Output Signal Connectors	SMA RF Input. A simple Stub Test Antenna is supplied BNC Input direct to Bit Synchroniser (+ 3V Max input amplitude) BNC input for IRIG B modulated Time Code Signal 4 pin RS422 data and clock output connector for recovered data and clock. RS422 input connector for external clock and data with stand alone USB Decommulator option. (mating halves provided)
Loop Bandwidth	0. 01% to >5% of bit rate (user programmable)
Tracking Range	Up to 10% (user programmable)
Bit Error Rate	Approaches 1 dB of ideal performance curve below 3 MBPS
Output Data	Decommuted IRIG 106 PCM data is transferred to the host PC through the high speed USB port
Software	Supplied with single stream USB version of GDSmate to enable the host PC to set up the unit and to provide graphical data displays. Archiving, Replay and Ethernet networking is also supported

System Interface Specification

Interface Type	USB 2 Bus. Backwards compatible with USB 1 ports
Power Requirements	Within USB Bus Hub limits
Software	Set-Up and controlled using the Apollotek GDSmate Telemetry Environment Software package (see separate data sheet)

Mechanical Specification

Overall Size	105 mm long by 55 mm wide and 50 mm high 3 slice assembly
Manufacturing Processes	Surface mount, FPGA and PIC internal PCB technology Enclosure machined from solid aerospace grade aluminium to provide very rugged packaging

Operational Environmental Specification

Temperature	-10 ^o Centigrade to +70 ^o Centigrade
Humidity	0 to 90% non-condensing

Non-operating

Temperature	-25 ^o Centigrade to +90 ^o Centigrade
-------------	--